

MASTOR - 1585

PROJEKTÖRLER



Quantity (pcs)	Power	Luminosu Flex	Color Temp.	Size
Led Adedi	Güç	Işık Akışı	Renk Sıcaklığı	Boyutlar
12	13 W	1813 LM	2700K-4000K-5000K-6000K-Yeşil-Mavi	80x160x185mm
12	18 W	2430 LM	2700K-4000K-5000K-6000K-Yeşil-Mavi	80x160x185mm
12	25 W	3250 LM	2700K-4000K-5000K-6000K-Yeşil-Mavi	80x160x185mm
12	37 W	4455 LM	2700K-4000K-5000K-6000K-Yeşil-Mavi	80x160x185mm

Input Voltage	Power Efficacy	Power Factor	Junction Temp	CRI	Working Environment	Weight
Şebeke Gerilimi	Verim	Güç Faktörü	Jonksiyon Sıcaklığı	Renksel Geri Veri	Çalışma Sıcaklığı	Ağırlık
AC 220V-240V	93%	> 0.95	< 85 C	Ra > +70 Ra > +80	-40 C -+ 60 C	1.15

Life Span	Overvoltage	Lens Angles	Size	Connection Holes	Body	IP Rating
Led Ömrü	Aşırı Gerilim	Lens Açılırları	Ölçüler (mm)	Bağlantı Delikleri	Gövde	Koruma Sınıfı
> 60.000 hours	6KV - 10 KV	15°-30°-45°-60°-90°-120°	80x160x185mm	60 mm	Alüminyum	IP66

